

MATERIAL SAFETY DATA SHEET**SECTION I: IDENTIFICATION OF PRODUCT**

COMPANY: **Diversity Technologies Corp.** DATE: Oct 31, 2006
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **CALCIUM CHLORIDE 94-97 %
 (HT FINES; HT POWDER; MINIPELLETS)**

PRODUCT USE: Oil well drilling fluid & cement additive
 CHEMICAL FAMILY: Inorganic calcium salt CAS#: 10043-52-4

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2B
 WORKPLACE HAZARD: Eye irritant

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
 TDG CLASSIFICATION: Not applicable
 UN NUMBER (PIN): Not applicable
 PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

| <u>INGREDIENT</u> | <u>PERCENT</u> | <u>CAS NUMBER</u> | <u>LD₅₀Oral-Rat</u> | <u>LC₅₀Inhal-Rat</u> | <u>ACGIH-TLV</u> |
|-------------------|----------------|-------------------|--------------------------------|---------------------------------|------------------|
| Calcium chloride | 94-97 | 10043-52-4 | 1000 mg/kg | No information | Not established |

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [XX]EYE CONTACT [XX]SKIN [XX]INHALATION [XX]INGESTION
 EYE CONTACT: Solid and concentrated liquid will cause moderate to severe eye irritation with corneal injury that may be slow to heal. **When dissolving, the heat produced may cause more intense effects as well as thermal burns.**

SKIN CONTACT: Prolonged or repeated contact with the dust may irritate the skin or cause burns especially if skin is moist or if material is confined to skin.

INGESTION: Oral toxicity considered low. Swallowing solids may cause gastrointestinal irritation or ulceration.

| | |
|------------------------|--|
| INHALATION: | Breathing dust may irritate the nose and throat and cause coughing and chest discomfort. |
| CARCINOGENICTY: | No information available |
| TERATOGENICITY: | No information available |
| REPRODUCTIVE TOXICITY: | No information available |
| MUTAGENICTY: | No information available |
| SYNERGISTIC PRODUCTS: | No information available |

SECTION IV: FIRST AID MEASURES

| | |
|---------------|--|
| EYE CONTACT: | Immediately flush with gently flowing warm water for 15 minutes. Obtain medical attention when flushing is complete. |
| SKIN CONTACT: | Wash affected area with soap and water. Remove contaminated clothing and shoes; wash before reuse. If irritation persists, or develops, obtain medical attention. |
| INGESTION: | Do not induce vomiting. Rinse mouth with water. Give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hips to ensure vomitus is not aspirated, then rinse mouth and readminister water. Obtain medical attention. Never give anything by mouth to an unconscious or convulsing victim. |
| INHALATION: | Move to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties, or distress, continue obtain medical attention. |

SECTION V: PHYSICAL DATA

| | | |
|-----------------------------|--------------------------------------|--------------------------|
| APPEARANCE AND ODOUR: | White to off-white powder, odourless | |
| SPECIFIC GRAVITY: | 2.2 | |
| BOILING POINT (C): | 1670 | |
| MELTING POINT (C): | 772 (approx) | |
| SOLUBILITY IN WATER: | Very soluble | pH: 8 – 9 (35% solution) |
| PERCENT VOLATILE BY VOLUME: | Not applicable | |
| EVAPORATION RATE: | Not applicable | |
| VAPOUR PRESSURE (mmHg): | Not applicable | |
| VAPOUR DENSITY (air = 1) | Not applicable | |
| BULK DENSITY: | Not available | |

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

| | |
|-------------------|----------------|
| FLASH POINT: | Not applicable |
| FLAMMABLE LIMITS: | Not applicable |

| | |
|-------------------------------------|--|
| EXTINGUISHING MEDIA: | Use media suitable for surrounding fire and packaging. |
| SPECIAL FIRE FIGHTING PROCEDURES: | Self-contained breathing apparatus required for fire fighting personnel. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | Hydrogen chloride is a hazardous combustion product at temperatures in excess of 1600°C. |

SECTION VII: REACTIVITY DATA

| | | |
|--|--|---------------|
| STABILITY: | STABLE [XX] | UNSTABLE [] |
| INCOMPATIBILITY (CONDITIONS TO AVOID): | May react violently with processed lime to produce heat. Corrosive to some metals. Corrosive when wet. Flammable hydrogen may be generated from contact with metals such as zinc or sodium. Avoid contact with sulfuric acid. Heat is generated when mixed with water. Splattering or boiling may occur. | |
| CONDITIONS OF REACTIVITY: | Not available | |
| HAZARDOUS DECOMPOSITION PRODUCTS: | None | |
| HAZARDOUS POLYMERIZATION: | WILL NOT OCCUR [XX] | MAY OCCUR [] |

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

| | |
|---------------------------------------|--|
| RESPIRATORY PROTECTION: | NIOSH/MESA approved dust mask or respirator if high dust levels expected. |
| VENTILATION: | Use local exhaust ventilation, process enclosure or other engineering controls to maintain dust level below TLV. |
| PROTECTIVE GLOVES: | Rubber gloves recommended. |
| EYE PROTECTION: | Chemical goggles recommended. |
| OTHER PROTECTIVE EQUIPMENT (Specify): | Full body covering recommended. Ensure eyewash and safety shower available. |

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Wash thoroughly after handling. Avoid contact with eyes, skin, or clothing. Store in a cool, very dry place; material is hygroscopic. Keep container tightly closed when not in use. Heat developed during diluting or dissolving is very high. Use cool water when diluting or dissolving. Empty packaging contains residual hazardous material and should be stored and handled as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Wear suitable protective equipment. Collect uncontaminated material for repacking. Collect contaminated material in an approved container for disposal. Wash residual material with copious amounts of water.

WASTE DISPOSAL METHOD

Dispose/landfill in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Empty containers contain residual chemical and must be disposed of or recycled in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: October 31, 2006 BY: Product Safety Committee
SUPERSEDES: October 31, 2003

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply Ltd., Hollimex Products Ltd. and Canamara SDS.**