



## Dry-X (Desiccated Wood Fibre)

### DESCRIPTION

**DRY-X** is a kiln-dried Sawdust product which exhibits greater absorption than conventional sawdust. This desiccated wood by-product swells up to  $\pm 3$  times its original volume when exposed to water.

### PROPERTIES

<b>Physical</b>		<b>Chemical</b>	
Appearance:	Wood By-Product	Type:	Wood
Specific Gravity:	0.27	Solubility:	No
Bulk Density	N/A	pH:	N/A
Moisture:	<5.0%	Microtox:	N/A
Flash Point:	3		
Pour Point:	N/A		

### APPLICATION

**DRY-X** may be used in all applications where conventional sawdust is used on drilling locations. Due to the degree of swelling of this product in the presence of a water based drilling fluid it may be more beneficial than generic sawdust in sealing loss zones on surface hole sections.

### MIXING AND HANDLING

**DRY-X** mixes readily and may be added to a mud system through the hopper at 10-15 minutes per sack. It may also be added directly down the hole through the rotary table, in the event of severe total losses.

It is advisable to use a dust mask and eye protection while mixing all powdered products.

<b>WHMIS:</b> Not Controlled	<b>TDG:</b> Not regulated	<b>PACKAGING:</b> 40 lb bag
------------------------------	---------------------------	-----------------------------